

BLD PROOF HYBRID



DESCRIPTION

BLD PROOF HYBRID is a high performance, liquid applied waterproofing membrane of modified polyurethane resin. It is specially formulated to waterproof and decorate exterior roofs. It consists of a flexible polymer and other carefully selected additives that allow the cured membrane to accommodate movements in the substrate. It works as a seamless membrane that seals cracks and joints in old or new roofs and provides a trafficable surface.



USES

- Exposed Concrete Slab Roofs
- Metal Surfaces
- Fibre Cement Boards
- Gutters
- New and Old Roofs
- Tiles Roofs

ADVANTAGES

- Easy to apply – brush, roller or airless spray can be used.
- Solvent Free – giving operators safe and clean working environment.
- Low VOC and Environmentally friendly.
- Waterproofing – protects new and old concrete from the passaging of water.
- Durability – enforced with fibre glass (or fleece) matt increases mechanical properties and wear resistance.
- Weather Resistant – excellent UV resistance.
Flexible, accommodates minor joint movements and enable bridging of
➤ hairlines cracks.

APPLICATION

INSTRUCTION FOR USE:

- Fresh concrete should be allowed to cure for at least 28 days before the application of BLD PROOF HYBRID with humidity not to exceed 8%.
- Ensure the surface is clean and free from dust, grease, oil or any loose material.
- Do not add any quantity of water.